# Automatic Thermostatic Shower Control SLS 03






#### **Characteristics**




- hygienic flush
- is destined for cold and hot water, temperature is regulated by thermostatic mixer
- with upper outlet
- safety fuse against scalding
- water is flowing as long as an user is in the active range
- water stops flowing after the user leaves the active range sensor after adjustable time delay (can be set in range 0,25 - 7,75 s), standard 3 s
- function of automatic water stop after 5 minut of continuous flow
- monitoring of battery capacity (for models with index B)
- START/STOP program
- parameter adjustment using by the remote control SLD 03

## **Installation Drawing**



- 1 water supply
- 2 active range
- 3 spout
- 4 chrome body
- 5 thermostatic mixer



SLS 03

### **Technical Specification**

Water inlet spacing
Operating voltage

SLS 03

■ SLS 03B

Power input

• operating by 24 V DC

operating by 9 V
 Battery life

lithium 9 V, type U9VL

- Intiliality v, type obv

**Active range** 

standardSTART/STOP program

Recommended flow pressure Water inlet

Water inlet Water outlet 150 mm

150 mm

24 V DC 9 V

3 W

2 W

approx. 2 years (100 uses per day)

0,6 - 0,75 m 0,05 - 0,15 m

0,1 - 0,6 MPa male thread G 1/2" male thread G 1/2"

## **Supply Specification**

SLS 03B -

SLS 03 - Supply No. 02030

shower control with electronics, thermostat and electromagnetic valve, rosette (2 pcs.),

chrome cover (2 pcs.), filter (2 pcs.), Alley key, lithium battery SLA 09 (SLS 03B)

#### **Recommended Accessories**

**Supply No. 02036** 

SLZ 01Y - Supply No. 05012 power supply 24 V DC for operating of max. 10 pcs. of showers power supply 24 V DC for operating of max. 20 pcs. of showers

SLZ 04Y - Supply No. 05042 power supply 24 V DC for DIN rail, for operating of max. 10 pcs. of showers
 SLZ 04Z - Supply No. 05041 power supply 24 V DC for DIN rail, for operating of max. 20 pcs. of showers
 SLZ 04X - Supply No. 10049 power supply 24 V DC for DIN rail, for operating of max. 33 pcs. of showers

SLD 03 - Supply No. 07030 remote control for an adjustment of parameters

SLA 09 - Supply No. 06090 lithium battery 9 V/1200 mAh, type U9VL (for models with index B)